

E FORCE 2.0™

THE NEXT GENERATION OF UNTETHERED EXTRICATION



GENESIS
RESCUE SYSTEMS

ART.107.526.2

NXTgen

C236 CUTTER

POWERED BY *Milwaukee*



SPECIFICATIONS

LENGTH (in/mm):	38.7/982
WIDTH (in/mm):	10.2/260
DEPTH (in/mm):	9.4/241
WEIGHT (lbs/kgs):	51.8/23.5
BLADE OPENING (in/mm):	7.9/200
OPERATING PRESSURE (psi/bar):	10,000/700
MAX CUTTING FORCE (lbf/kN):	236,000/1,050
NFPA 1936 LEVEL RATING:	A8/B9/C8/D9/E9
NFPA COMPLIANT:	YES

NXTgen™ BLADE INSERTS

The cutting performance of any cutting blade begins with a sharp edge. It was with this thought; Genesis Rescue Systems set out to engineer and manufacture a solution to degraded cutting performance due to the rounding of the blade edge. Without sacrificing quality we created the NXTgen Blade Insert.

NXTgen ART.107.525.5 C185 CUTTER

POWERED BY *Milwaukee*



 **E-FORCE 2.0™**

SPECIFICATIONS

LENGTH (in/mm):	35/889
WIDTH (in/mm):	9.3/236
DEPTH (in/mm):	9.5/241
WEIGHT (lbs/kgs):	47.2/21.4
BLADE OPENING (in/mm):	7.1/180
OPERATING PRESSURE (psi/bar):	10,000/700
MAX CUTTING FORCE (lbf/KN):	203,175/903
NFPA 1936 LEVEL RATING:	A7/B9/C7/D9/E9
NFPA COMPLIANT:	YES

WWW.GENESISRESCUE.COM



GENESIS
RESCUE SYSTEMS

ART.107.202.6

C165 CUTTER

POWERED BY *Milwaukee*

BC **EFORCE 2.0™**

SPECIFICATIONS

LENGTH (in/mm):	33.3/845
WIDTH (in/mm):	9.3/236
DEPTH (in/mm):	9.5/241
WEIGHT (lbs/kgs):	43/19.5
BLADE OPENING (in/mm):	5.9/150
OPERATING PRESSURE (psi/bar):	10,000/700
MAX CUTTING FORCE (lbf/kN):	144,450/642
NFPA 1936 LEVEL RATING:	A8/B5/C6/D7/E9
NFPA COMPLIANT:	YES



ART.107.202.1

17C VARIO

POWERED BY 



 **EFORCE 2.0™**

SPECIFICATIONS

LENGTH (in/mm):	37/940
WIDTH (in/mm):	9.3/235
DEPTH (in/mm):	9.5/241
WEIGHT (lbs/kgs):	48.3/21.9
SPREADING DISTANCE (in/mm):	16.5/420
OPERATING PRESSURE (psi/bar):	10,000/700
MAX SPREADING FORCE (lbf/kN):	160,055/726
MAX CUTTING FORCE (lbf/kN):	115,965/526
NFPA 1936 LEVEL RATING:	A7/B9/C7/D9/E9
NFPA COMPLIANT:	YES



WWW.GENESISRESCUE.COM

GENESIS
RESCUE SYSTEMS

ART.107.445.8

14C VARIO

POWERED BY *Milwaukee*

MECHANICAL RAM FOR 11C & 14C
ART.105.647.8

EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	35.9/914
WIDTH (in/mm):	9.3/236
DEPTH (in/mm):	9.5/236
WEIGHT (lbs/kgs):	41/18.6
SPREADING DISTANCE (in/mm):	14.2/360
OPERATING PRESSURE (psi/bar):	10,000/700
MAX SPREADING FORCE (lbf/KN):	176,025/783
MAX CUTTING FORCE (lbf/KN):	110,381/491
NFPA 1936 LEVEL RATING:	A6/B8/C6/D8/E7
NFPA COMPLIANT:	YES



ART.107.767.6 15C VARIO

POWERED BY *Milwaukee*

EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	36.2/920
WIDTH (in/mm):	9.3/236
DEPTH (in/mm):	9.5/241
WEIGHT (lbs/kgs):	42.8/19.4
SPREADING DISTANCE (in/mm):	14.4/365
OPERATING PRESSURE (psi/bar):	10,000/700
MAX SPREADING FORCE (lbf/KN):	176,025/783
MAX CUTTING FORCE (lbf/KN):	110,381/491
NFPA 1936 LEVEL RATING:	A6/B8/C6/D8/E7
NFPA COMPLIANT:	YES

15C VARIO IS NOT COMPATIBLE WITH MECHANICAL RAM



WWW.GENESISRESCUE.COM
GENESIS
RESCUE SYSTEMS

ART.107.526.3

S45 SPREADER

POWERED BY *Milwaukee*

EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	36.4/924
WIDTH (in/mm):	9.6/243
DEPTH (in/mm):	9.5/241
WEIGHT (lbs/kgs):	40.4/18.3
OPERATING PRESSURE (psi/bar):	10,000/700
SPREADING DISTANCE (IN/MM):	23.6/600
MAX SPREADING FORCE (lbf/KN):	38,250/170
LOWEST SPREADING FORCE (lbf/KN):	8,093/36
NFPA COMPLIANT:	YES

ART.107.779.1 S53 SPREADER

POWERED BY *Milwaukee*



EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	39.1/993
WIDTH (in/mm):	11.7/298
DEPTH (in/mm):	9.4/240
WEIGHT (lbs/kgs):	52.9/24
OPERATING PRESSURE (psi/bar):	10,000/700
SPREADING DISTANCE (IN/MM):	31.5/800
MAX SPREADING FORCE (lbf/kN):	94,725/421
LOWEST SPREADING FORCE (lbf/kN):	11,870/52.8
NFPA COMPLIANT:	YES



WWW.GENESISRESCUE.COM
GENESIS
RESCUE SYSTEMS

22/54 TELESCOPIC RAM

POWERED BY *Milwaukee*

ART.107.834.2

EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	22/560
WIDTH (in/mm):	5.3/134
DEPTH (in/mm):	13.7/347
WEIGHT (lbs/kgs):	41.4/18.8
OPERATING PRESSURE (psi/bar):	10,000/700
LENGTH EXTENDED (IN/MM):	53.5/1360
STROKE (lbf/KN):	31.5/800
MAX PUSHING FORCE (lbf/KN):	24,279/108
NFPA COMPLIANT:	YES

22/54 EFORCE TELESCOPIC RAM IS NOT COMPATIBLE WITH THE ANGLED V-HEAD ATTACHMENTS

ART.107.527.2 21/36 RAM

POWERED BY *Milwaukee*



EXTENSIONS AVAILABLE
7 INCH - ART.105.848.2
10 INCH - ART.383.857.9
12 INCH - ART.106.244.2

FEATURED WITH THE PATENTED
ANGLED V-HEAD ATTACHMENTS
ART.011.130.2 - THREADED
ART.011.130.4 - SLIP FIT

E-FORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	21.3/542
WIDTH (in/mm):	5.3/134
DEPTH (in/mm):	12.8/325
WEIGHT (lbs/kgs):	34.6/15.7
LENGTH EXTENDED (in/mm):	35.8/910
OPERATING PRESSURE (psi/bar):	10,000/700
STROKE (IN/MM):	14.6/370
MAX PUSHING FORCE (lbf/kN):	25,021/111.3
NFPA COMPLIANT:	YES



WWW.GENESISRESCUE.COM

GENESIS
RESCUE SYSTEMS

ART.107.525.0
11C VARIO

POWERED BY *Milwaukee*

MECHANICAL RAM FOR 11C & 14C
ART.105.647.8

EFORCE 2.0™

SPECIFICATIONS

LENGTH (in/mm):	31.4/798
WIDTH (in/mm):	7.5/192
DEPTH (in/mm):	9.4/240
WEIGHT (lbs/kgs):	31.3/14.2
SPREADING DISTANCE (in/mm):	10.4/265
OPERATING PRESSURE (psi/bar):	10,000/700
MAX SPREADING FORCE (lbf/kN):	132,975/591
MAX CUTTING FORCE (lbf/kN):	72,838/324
NFPA 1936 LEVEL RATING:	A6/B5/C6/D6/E7
NFPA COMPLIANT:	YES



EXTRICATION BACKPACK
ART.EXTBP



DOOR OPENER

ART.107.814.0

POWERED BY *Milwaukee*

SPECIFICATIONS

LENGTH (in/mm):	22.6/574
WIDTH (in/mm):	7.6/194
DEPTH (in/mm):	9/230
WEIGHT (lbs/kgs):	31.5/14.3
STROKE (in/mm):	5.5/140
OPERATING PRESSURE (psi/bar):	10,000/700
MAX PUSHING FORCE (lbf/KN):	23,649.9/105.2
NFPA COMPLIANT:	NA



CONCRETE CRUSHER

ART.107.772.1

POWERED BY *Milwaukee*

SPECIFICATIONS

LENGTH (in/mm):	34.5/878
WIDTH (in/mm):	10.3/262
DEPTH (in/mm):	11.9/303
WEIGHT (lbs/kgs):	47.4/21.5
BLADE OPENING (in/mm):	9.8/250
OPERATING PRESSURE (psi/bar):	10,000/700
MAX CRUSH FORCE (lbf/KN):	25,504/109
MIN CRUSH FORCE (lbf/KN):	15,736/70
NFPA COMPLIANT:	NA



POWER WEDGE

ART.107.781.2

POWERED BY *Milwaukee*

SPECIFICATIONS

LENGTH (in/mm):	29.8/758
WIDTH (in/mm):	5.9/150
DEPTH (in/mm):	9.4/240
WEIGHT (lbs/kgs):	27.8/12.6
SPREADING DISTANCE (in/mm):	2.4/61
OPERATING PRESSURE (psi/bar):	10,000/700
MAX SPREADING FORCE (lbf/KN):	55,800/248
NFPA COMPLIANT:	YES



E28 E-PACK

ART.110.100.07

POWERED BY **GENESIS**
RESCUE SYSTEMS

AVAILABLE IN BLACK - ART.110.100.0B



SPECIFICATIONS

LENGTH (in/mm):	10.17/258
WIDTH (in/mm):	7.7/195
DEPTH (in/mm):	4.4/112
EPACK WEIGHT (lbs/kgs):	7.2/3.3
CABLE LENGTH (in/mm):	15/4.6
CABLE WEIGHT (psi/bar):	3.7/1.7
TOTAL WEIGHT (lbf/KN):	10.9/5
VOLTAGE:	28 V
AMP HOURS:	13 Ah
WATT HOURS:	335 Wh

AC ADAPTER

110 VAC - ART.106.042.6
220 VAC - ART.106.042.2



12V-28V 3 BAY CHARGER

110 VAC - ART.105.410.8



12V-28V 1 BAY CHARGER

110 VAC - ART.105.409.7

220 VAC - ART.105.409.5

12 VDC - ART.106.042.3



5 AH E28 LITHIUM

ART.105.378.5

POWERED BY **GENESIS**



SPECIFICATIONS

LENGTH (in/mm):	3.3/84
WIDTH (in/mm):	3.2/81
DEPTH (in/mm):	5.26/134
WEIGHT (lbs/kgs):	2.2/1
VOLTAGE:	28 V
AMP HOURS:	5 Ah
WATT HOURS:	84 Wh
WARRANTY:	3 YEAR

5 AH M28 LITHIUM

ART.105.375.5

POWERED BY **MILWAUKEE**



SPECIFICATIONS

LENGTH (in/mm):	3.3/84
WIDTH (in/mm):	3.2/81
DEPTH (in/mm):	5.3/134
WEIGHT (lbs/kgs):	2.3/1
VOLTAGE:	28 V
AMP HOURS:	5 Ah
WATT HOURS:	140 Wh
WARRANTY:	3 YEAR

WWW.GENESISRESCUE.COM



GENESIS
RESCUE SYSTEMS



GENESIS

RESCUE SYSTEMS

WWW.GENESISRESCUE.COM

2780 CULVER AVENUE
KETTERING, OHIO 45429
UNITED STATES



LOOKING FOR FREE TRAINING ?
SCAN THE CODE

